



## EO MINI PRO 3

Impossibly small.  
Impressively smart.

## EO MINI PRO 3

DESIGNED AND MANUFACTURED  
IN THE UNITED KINGDOM.



## FEATURES

- + Connection type: Universal Type 2 socket, Type 1 and Type 2 tethered cable (5m)
- + Power ratings: Single-phase up to 7.2kW (Type 1 & Type 2), three-phase up to 22kW (Type 2 only)
- + Solar charging: Charge your car with our solar matching or net-zero technologies (optional extra, using an additional CT clamp)<sup>1</sup>
- + Connectivity: Wi-Fi, Cat 5 Ethernet, Bluetooth as standard, 4G cellular<sup>1</sup> as optional extra
- + Integrated RFID reader & EO branded RFID tags available (optional)<sup>1</sup>

## INSTALLATION

- + Simple electrical installation
- + Integral 6mA DC leakage detection, no Type B RCD required
- + Adjustable maximum charging current for lower rated supplies
- + TN & IT grid connections

## INTELLIGENCE

- + OCPP 1.6J: Back-office agnostic, ready for open OCPP integration and additional security extensions
- + Built-in power balancing with OCPP or locally via CT clamp
- + ISO15118 ready for vehicle-to-grid (V2G) and plug & charge functionality<sup>1</sup>
- + EO Hub 2: Connect an unlimited number of chargers to the EO Hub 2<sup>1</sup> for small commercial installations and additional load management
- + Smartphone app controlled: Energy usage monitoring and charging sessions management using our iOS and Android smartphone app

<sup>1</sup>Feature not available with V1 product. V2 coming soon.

